

## ::: **KS-300**

cavity protection wax

### **CHARACTERISTICS**

Car System Underbody Protection Wax has a hydrophobic and penetrating effect. Once the solvent evaporates, the product leaves a slightly sticky, glazed wax-like film. The whitish-translucent film is elastic and will withstand extreme atmospheric conditions.

Car System Underbody Protection Wax has excellent heat resistance and can therefore be used on parts of the engine as well.

### **APPLICATION**

Liquid anti-corrosion product specially developed to preserve vehicle cavities using the Swedish "ML" method. Use as a cavity protector for vehicles and as a general anti-corrosion agent for long-term storage of machine parts, tools, machines and devices in automotive shops, metal shops, body shops, and other industrial areas, particularly when items are stored outdoors.

### **PRODUCT DATA**

Packaging: 1000 mL container

Color: Whitish-transparent

High melting point: 160°C

Flash point: 41 °C

Density (20°C): 0.85 g/cm<sup>3</sup>

Specific gravity: Ca. 0,85 kg/l

The drying time depends on the layer thickness and ambient conditions. When hard, the product remains smooth and tacky.

Solids content: Ca. 48%



05/2017

## HANDLING

Apply Car System Underbody Protection Wax by immersing the parts, painting the spray on with paintbrushes, or using non-pressurized sprayers with special nozzles or suction spray guns. It is easy to apply, does not drip, and provides maximum protection when applied in thin layers.

## SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE